

**Battery powered plastic strapping tool for demanding applications**

---

**Characteristics**

---

Strapping qualities:	Polyester (PET) and Polypropylene (PP) plain and embossed
Strapping dimensions:	width 16.0 ± 19.0 mm / 5/8 ± 3/4' thickness 0.65 ± 1.35 mm / .026 ± .053'
Weight incl. battery:	4.2 kg / 9.3 lbs
Tool size with battery:	L351 x W134 x H143 mm _ ____' [ __3' [ __6'
Type of seal:	Friction weld sealing
Average seal strength:	approx. 75% (dependent on strap quality)
Tension force:	500 ± 4000 N / 112 ± 900 lbs (adjustable)
Tension speed:	49 ± 79 mm/s / 1.9 ± 3.1 inch/s
Power supply:	Battery Li-Ion 18VDC / 4.0 Ah
Suspension bracket:	optional

**Advantages**

---

- High tension force up to 4000N / 900 lbs
- Tension force and sealing time adjustable with simple knobs
- Tool in both semi-automatic and automatic (single button) version available for efficient operation
- Brushless motor for less maintenance and improved life time
- Improved plates and guides ± less effort to remove the tool from the strap
- No tension rocker ± easier to remove tool from small package surfaces
- Motor temperature monitoring to protect motor from overheating
- Cycle counter included (special reader required)
- Battery well protected
- Battery charge indicator included
- Simple one-handed operation
- Tool is fully covered for finger protection
- Optional motor cooling fan available to reduce overheating risk

**Chart of types model P329**

Item no.	Model	Strap widths		Strap thicknesses		Max. tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
43.2522	P329/16/0.65-1.05	16	5/8	0.65-1.05	.026-.041	4000	900	49-79	1.9-3.1
43.2532	P329/19/0.65-1.05	19	3/4	0.65-1.05	.026-.041	4000	900	49-79	1.9-3.1
43.2533	P329/19/1.06-1.35	19	3/4	1.06-1.35	.042-.053	4000	900	49-79	1.9-3.1
43.2722	P329/16/0.65-1.05/A	16	5/8	0.65-1.05	.026-.041	4000	900	49-79	1.9-3.1
43.2732	P329/19/0.65-1.05/A	19	3/4	0.65-1.05	.026-.041	4000	900	49-79	1.9-3.1
43.2733	P329/19/1.06-1.35/A	19	3/4	1.06-1.35	.042-.053	4000	900	49-79	1.9-3.1

**A = Automatic model**

**Battery chargers for model P329**

Item no.	Model	Voltage / frequency	Countries
N5.4443	Li-Ion battery charger	220-240 V / 50-60 Hz	A, B, BG, BIH, BOL, BR, BY, CH, CL, CZ, D, DK, DZ, E, EAS, EST, ET, F, FIN, GE, GR, H, HK, HR, I, IL, IND, IR, IRQ, IS, JOR, KSA, KWT, L, LAR, LT, LV, MA, MC, MK, MOC, N, NL, P, PK, PE, PL, PRC, PY, RA, RCH, RI, RL, RO, ROK, ROU, RP, RUS, S, SK, SLO, SYR, THA, TN, TR, UA, UAE, YU, YV, (BRN), (BRU), (CY), (EAK), (EAT), (GB), (IRL), (M), (MAL), (OM), (SGP), (Y), (Z), (ZA), (ZW)
N5.4447	Li-Ion battery charger	120 V / 50-60 Hz	BR, C, CDN, CO, CR, DOM, EC, GCA, J, JA, KSA, LB, MEX, NIC, PA, Puerto Rico, RC, RP, USA, YV
N5.4445	Li-Ion battery charger	220-240 V / 50-60 Hz	AUS, NZ

(..) = Adapter N52.2102 required

**Battery for model P329**

Item no.	Battery	Voltage	Capacity	Charging time
N5.4349	Accu Li-Ion	18VDC	4.0 Ah	approx. 80 min.

**Accessories**

P32.0223	Suspension bracket
P32.0226	Wearing plate (metal) for rough and hard surfaces
P32.0227	Protection plate (plastic) to protect complete bottom side
P32.0228	Motor cooling fan
N7.5154	Cycle count reader