

Manual sealless steel strapping tool



Characteristics

| | |
|------------------------|---|
| Strapping qualities: | Uniflex regular duty max. 850 N/mm ² / 123'000 psi |
| Strapping dimensions: | widths 12.7 – 20.0 mm / ½ - ¾" |
| thicknesses | 0.38 – 0.58 mm / .015 – .023" |
| Weights: | 3.9 kg / 8.6 lbs Normal version 4.3 kg / 9.5 lbs TW version |
| Average seal strength: | approx. 80 % |
| TW-version available: | Torque wrench tensioning system |
| Suspension (Optional): | Bolt and grip ball for horizontal applications; have to be ordered separately Suspension bracket for vertical applications; has to be ordered separately |

Advantages

- Handy light weight sealless combination tool to strap flat packages (i.e. pallets, bales, crates, cases, various packages)
- Permits a very easy and efficient operation and outperforms other strapping tools by its ruggedness and its high reliability
- The sealless joint reduces the overall strapping costs by approx. 10% through the elimination of the seals

Chart of types model A333 and A333/TW

| Item No. | Model | Uniflex max. 850 N/mm ² / 123'000 psi | | | |
|----------|------------------------|---|------|-------------|-----------|
| | | Width | | Thicknesses | |
| | | mm | inch | mm | inch |
| 13.2370 | A333/12.7/0.38-0.58 | 12.7 | 1/2" | 0.38-0.58 | .015-.023 |
| 13.2380 | A333/13/0.38-0.58 | 13.0 | | 0.38-0.58 | .015-.023 |
| 13.2390 | A333/16/0.38-0.58 | 16.0 | 5/8" | 0.38-0.58 | .015-.023 |
| 13.2410 | A333/19/0.38-0.58 | 19.0 | 3/4" | 0.38-0.58 | .015-.023 |
| 13.2420 | A333/20/0.38-0.58 | 20.0 | | 0.38-0.58 | .015-.023 |
| 13.2371 | A333/12.7/0.38-0.58/TW | 12.7 | 1/2" | 0.38-0.58 | .015-.023 |
| 13.2381 | A333/13/0.38-0.58/TW | 13.0 | | 0.38-0.58 | .015-.023 |
| 13.2391 | A333/16/0.38-0.58/TW | 16.0 | 5/8" | 0.38-0.58 | .015-.023 |
| 13.2411 | A333/19/0.38-0.58/TW | 19.0 | 3/4" | 0.38-0.58 | .015-.023 |
| 13.2421 | A333/20/0.38-0.58/TW | 20.0 | | 0.38-0.58 | .015-.023 |

TW = Torque wrench tensioning system

Accessories

- A33.4101 Bolt for horizontal applications
(in combination with grip ball N4. 1116)
- N4.1116 Grip ball for horizontal applications
(in combination with bolt A33.4101)
- A33.0113 Suspension for vertical applications